

A Retractable Device for Sun Shading Suspensory Umbrella

FIELD OF THE INVENTION

The present invention relates to a retractable device for outdoor umbrella, and more particularly, to an improved retractable device of stretch and closure for large size
5 sun shading suspensory umbrella used in a beach environment or the like .

BACKGROUND OF THE INVENTION

Owing to its huge panel and ribs, a conventional large size sun shading suspensory
10 umbrella used in a beach environment or the like is difficult to control its stretch and closure, so it becomes the key point of using and the selection of umbrella. Various of stretch and closure structures of umbrella are available in the umbrella making field, but all existing structures of hand cranking device are in a model of ratchet and pawl. The solution of the stretch and closure structures of umbrella is mainly laid to frictional force.
15 There are many defects in said existing structures, such as 1. frictional force is insufficient or not stable, resulting in disengagement or retroflexion in the stretching of sun shading umbrella; 2. frictional force made the abrasion of the parts, impacting its service life; 3. it is heavy and hard to stretch sun shading umbrella by cranking. 4. sometimes umbrella can not be complete contracted and closed by gravity. The present invention intends to provide
20 a convenient stretch and closure structure of sun shading suspensory umbrella to overcome the disadvantages of conventional structure of umbrella.

SUMMARY OF THE INVENTION

In accordance with one aspect of the present invention, there is provided a retractable device of sun shading suspensory umbrella mainly comprising an upper and
5 lower support umbrella rods, ribs and hand cranking device.

The diameter of said upper support umbrella rod is less than said lower support umbrella rod, said upper umbrella rod is located within the low portion of said retractable device, said hand cranking retractable device is equipped within lower portion of said
10 lower support umbrella rod, said hand cranking retractable device is a worm with a handle, which connects with an active worm gear and a driven worm gear separately on both sides, said active worm gear and driven worm gear separately connects to entwined wire rope rotating wheel A and B through axletree, one end of said wire rope A is wired to rotating wheel A, the other end is securely mounted to lower umbrella tray, one end of said wire
15 rope B is wired to rotating wheel B, the other end of said wire rope B is securely mounted to upper support umbrella rods..

The advantages of the present invention are as follows: 1. The high performance of self-locking by adopting said worm gear and worm structure, not appearing the
20 phenomena of disengage and retroflexion in stretching the sun shading umbrella; 2. Structure tightness, and less mechanical wear, long performance life; 3. Adopting structure of said one worm to drive two worm gears, it is even more convenient to stretch and close by external action, moreover cranking is easiness and labor saving; 4. Said support umbrella rods are composed by two arc-shaped support rods, so that it is rich in
25 aestheticism and can stretch out and draw back freely.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will become more fully understood from the detailed description given hereinbelow and the accompanying drawings which are given by way of illustration only, and thus are not limitative of the present invention, and wherein:

FIG. 1 is an illustrative view to show closure state of the umbrella of the present invention;

10 FIG. 2 is an illustrative view to show stretch state of the umbrella of the present invention;

FIG. 3 is an illustrative view to show the structure of a hand cranking of the umbrella of the present invention;

15 FIG. 4 is a sectional view to show the structure of a hand cranking of the umbrella of the present invention;

FIG. 5 is a sectional view to show the structure of upper and lower support umbrella rods; and

20

FIG. 6 is an illustrative view to show the structure of ribs.

25 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Further scope of the applicability of the present invention will become apparent from the detailed description given hereinafter. However, it should be understood that the

detailed description and specific examples, while indicating preferred embodiments of the invention, are given by way of illustration only, since various changes and modifications *within the spirit and scope of the invention will become apparent to those skilled in the art* from this detailed description.

5

Referring to FIGS. 1 to 6, the retractable umbrella of the present invention comprises (1) wire rope, (2) rotating wheel A, (3) active worm gear, (4) worm, (5) axletree, (6) driven worm gear, (7) capping, (8) rotating wheel B, (9) shell, (10) wire rope A, (11) upper support rod assistant slide device, (12) wire-rope sheaves, (13) lower support umbrella rod, (14) upper support umbrella rod , (15) protective hood, (16) wire rope feed back pulley, (17) set bolt, (18) lower support rod assistant slide device, (19) wire rope fixed bolt, (20) lower umbrella tray and (21) handle.

The diameter of acambered upper support umbrella rod (14) is less than acambered lower support umbrella rod (13), upper support umbrella rod is located within the lower support umbrella rod (13) and is retractable. A assistant sliding device (11) is located in the lower part of upper support umbrella rod (14). Said sliding device (11) is composed of plastic sheath (111) and steel balls (112) which are evenly distributed to outside of the plastic sheath (111). Said steel balls (112) are able to roll, so that the frictional force may be decreased, when the said upper support umbrella rod (14) stretches out of lower support umbrella rod (13) and slides into lower support umbrella rod (13). There are three wire rope sheaves (12) within the lower portion of upper umbrella rod (14), so that the resistance force decreases when wire rope A1 is sliding; A assistant sliding device (18) is located within the upper portion of lower support umbrella rod (13), and the said sliding device (18) is composed of plastic sheath (181) and steel balls (182) which are evenly distributed to outside of the plastic sheath(181). There is a wire rope feed back pulley (16) located on external upper side of lower support umbrella rod (13) with a protective hood (15)outside, On the opposite side it has a set bolt (17).

Said hand cranking retractable device equipped with shell (9) and capping (7)
 locates within lower portion of the lower support umbrella rod (13), the said device is
 equipped with a worm (4) with a handle (21), the said worm (4) is separately
 5 connected an active worm gear (3) and a driven worm gear (6) on both sides,
 composing a structure of single worm driving two worm gears which are rotating in
 reverse directions. Said active worm gear (4) and driven worm gear (6) separately
 through axletree (5) connect to rotating wheel (A2) and rotating wheel B8 of entwining
 wire rope (A1) and wire rope (B10), one end of wire rope (A1) is connected to rotating
 10 wheel (A2), The other end is securely mounted to the lower tray (20) of the bins, one end
 of wire rope (B10) is connected to rotating wheel (B8), The other end of wire rope (B10)
 is fixed on upper support umbrella rod (14) by bolt (19). The rotating speed of active
 worm gear (4) is twice of the driven worm gear. The length of entwined wire rope (B10)
 on the rotating wheel (B8) is half of the travel length of wire rope (A1) in the closure
 15 condition of umbrella.

When users want to use the umbrella, if need to open umbrella, clockwise cranking
 handle (21) connected with worm (4), drive active worm gear (3) and driven worm
 gear (6) rotates in reverse direction, resulting the connected rotating wheel (A2) and
 20 rotating wheel (B8) to rotate in reverse directions synchronistically, at this point wire
 rope (A1) set on the umbrella tray (20) starts to entwine on the rotating wheel (A2), at
 the same time wire rope (B10) originally entwined on the rotating wheel (B8) starts to
 release, at this movement through wire rope sheaves (12) and wire rope feed back pulley
 (16), wire rope (A1) stretches upper support umbrella rod (14) out of the lower support
 25 umbrella rod (13), up to set bolt (17), by now upper support umbrella rod (14) is
 completely stretched out of the lower support umbrella rod (13) and the panel is also at
 full length.

If need to close the umbrella, the users are only required to crank the handle (21) connected to the worm (4), driving active worm gear (3) and driven worm gear (6) to rotates in reverse direction, resulting the connected rotating wheel (A2) and rotating wheel (B8) to rotate in reverse directions synchronistically, by this time, wire rope (B10)
 5 on the bolt (19) which is fixed on the upper support umbrella rod (14) starts to entwine to the rotating wheel (B8), at the same time wire rope (A1) originally entwined on the rotating wheel (A2) starts gradually to release, the upper support umbrella rod (14) is retract back into lower support umbrella rod (13) , plane will also close along with it, by now the length of the wire rope (B10) entwined on the rotating wheel (B8) is half of
 10 the whole travel length of the wire rope A, there is no entwined wire rope on the rotating wheel (A2), and it returns to its initial position.

The invention being thus described, it will be obvious that the same may be varied in many ways. Such variations are not to be regarded as a departure from the spirit and scope
 15 of the invention, and all such modifications as would be obvious to one skilled in the art are intended to be included within the scope of the following claims.